

Customer: PRIVATE CUSTOMER
 Sales manager: Ingvar Hansson
 Date created: 08-02-28
 Latest revision: 09-06-01
 Approved: 09-06-01 by PEW

Series production OK

General rig description

Conventional	Fractional
Keelstepped	1-spreader
Tapered	Sloop

Rig dimensions

Forestay height	FH:	9 915 mm
Main sail luff length	P:	11 700 mm
Boom height above deck	BH:	800 mm
Bury	Q:	1 100 mm
Main sail foot length	E:	4 800 mm
Main boom sheet pos	S:	4 300 mm
Spinnaker pole length	SPL:	2 580 mm

Chainplates dist. from cl mast

Lateral Long

Cap shrouds:	920	5 mm (0,3°)
Aft lowers:	920	160 mm
Deck above chainplates:	55 mm	
Deck above waterline:	1000 mm	

Hull and righting moment

Length:	10 180 mm
Beam:	2 060 mm
Draft:	1 620 mm
Displacement:	3 200 Kg
Ballast:	1 860 Kg
Conventional keel	
Equipped boat	
Heeling test RM:	13,7 kNm @30°

Spar sections

Mast:	C156
Boom:	B152
Spin. pole:	S048

Furlex

Forestay: 105

Notes (4 lines)

Forward jumper: 35 deg fwd.

Heeling test RM includes 3 crew members on rail and empty boat.

